

# E-901EI-F series

6th/7th/8th/9th Generation Intel® Xeon®/Core™ i7/i5/i3 Processor, Fanless, Embedded System



GE-901EI-F




GE-901EI-FL



GE-901EI-FC



GE-901EI-FG




## Product Features

- ◆ Industrial-grade Intel® Q170 SoC, compatible with Intel® Xeon®/Core™ desktop processors (6th/7th/8th/9th Gen)
- ◆ Fanless design, support -20°C~60°C working temperature
- ◆ 2\*DDR4 SO-DIMM, up to 32GB, dual channel support
- ◆ VGA, HDMI and DP interface, up to 4K 60Hz resolution
- ◆ 1\*M.2 B-Key supports 4G/3G, 1\*M.2 E-Key supports WIFI
- ◆ 1\*M.2 M-Key storage interface, support SATA3.0/NVMe protocol
- ◆ 1\* 2.5-inch hard drive extraction box, built-in a 2.5-inch hard drive, support SATA3.0
- ◆ 3\*intel high-performance Gigabit Ethernet ports, support up to 9 Ethernet ports (daughter board)
- ◆ 4\*COM(COM2/3 RS-232/422/485), support up to 8COM(sub board)
- ◆ Wide voltage power supply DC 9-48V, with short circuit, over voltage and over current protection

## Product Specifications

System	CPU	Intel® 6 <sup>th</sup> /7 <sup>th</sup> /8 <sup>th</sup> /9 <sup>th</sup> Gen Core™ i7/i5/i3/Pentium/Celeron LGA1151 processor, up to 8 cores and 16 threads	
	Chipset	Intel® Q170 Chipset	
	System Memory	2*260-Pin SODIMM, DDR4 2666/2400MHz, maximum support 32GB	
	Expansion Ports	1*USB2.0 built-in, support dongle 1*M.2 E-Key 2230, support Gigabit WFI module 1*M.2 B-Key 2242/2252 can support PCIe/USB/external SIM card, support 4G and other wireless functions	
	Display	Intel UHD Graphics, Supports DirectX11.1, OpenGL 5.0 and OpenCL 2.1 or PCIe X16 graphics card Display interface DP maximum resolution 4096*2304@60Hz, HDMI maximum resolution 4096*2160@24Hz, VGA maximum resolution 1900*1200@60Hz	
	Audio	Realtek ALC662 HD audio, Audio out and MIC, support 5.1 channel	
	Ethernet	1*Intel I211AT PCIe Gigabit Ethernet; 10/100/1000Mbps adaptive; 1*Intel I211AT PCIe Gigabit Ethernet; 10/100/1000Mbps adaptive 1*Intel I219LM PCIe Gigabit Ethernet; support iAMT12.0	
	Storage	1*2.5" SATA3 hard disk extraction box, supports up to 6G bit/s transfer speed; 1*2.5"HDD, support 5~9.5mm, built-in 1*M.2 M-Key storage interface, support M.2 2242/2280 NVME PCIE standard SSD	
	Expansion Daughter Board	Optional USB3.0/2.0, RJ45, 16-bit GPIO, remote switch and status indicator, or serial port	
	I/O ports	3*RJ45 Giga-LAN 6*USB3.0 TYPE A, up to 5G bit/s transmission speed, 4*USB2.0 built-in pins, 1*LPT built-in pin, 1*PS/2 built-in pin 2*RS232/422/485 set by BIOS, 2*RS232, 2*RS232 built-in pins 1*Audio-out and 1*MIC 1*VGA+1*DP+1*HDMI	
	Indicators	1*Power indicator, 1*HDD status indicator	
	Control Switch	1*Power SW, 1*Clear CMOS SW	
	Power Requirements	DC IN 9-48V 4-pin Term. 5.08mm, with short circuit, over voltage and over current protection Power consumption: TBD	
	TCPPM/TPM	optional support TPM2.0	
	Watchdog Timer	Watchdog Timer Programmable time-out interrupt or system reset, 1 to 255 seconds	
Operating System	Windows* 10 Enterprise & IOT Enterprise (64-bit) Ubuntu*、SuSe*、Redhat Enterprise* 1,2 Wind River* VxWorks* 7		
Box Structure	Construction	Aluminum rectangular heat dissipation shell, SGCC box	
	Color	dark blue + castor	
	Installation Method	Desktop	
	Size	(L*W*H): 248*235*77mm, with hanging ear : 248*264.6*80mm	
	Net Weight	5±0.2 ( unit : KG )	
Environment	Working Temperature	-20 ~ 65°C, wide temperature SSD, air flow -10 ~ 55°C, normal temperature HDD, air flow	
	Storage Temperature	-40°C~85°C	
	Storage Humidity	10~90%, non-condensing	

**Product Size** unit: mm



**Order Information**

Model	
GE-901EI-F	Barebone system, Intel®6/7/8/9代 LGA1151 CPU, Q170/C236, 3*LAN, 6USB3.1 , 4*COM,1*VGA, 1*DP, 1*HDMI, Audio out, Mic ,DC 9-48V
GE-901EI-FL	Barebone system, Intel®6/7/8/9代 LGA1151 CPU, Q170/C236, 7LAN, 6USB3.1 , 4*COM, 1*VGA, 1*DP, 1*HDMI, Audio out, Mic,DC 9-48V
GE-901EI-FC	Barebone system, Intel®6/7/8/9代 LGA1151 CPU, Q170/C236, 3AN,10USB3.1 , 8*COM, 1*VGA, 1*DP, 1*HDMI, Audio out, Mic,DC 9-48V
GE-901EI-FG	Barebone system, Intel®6/7/8/9代 LGA1151 CPU, Q170/C236, 3*LAN, 6USB3.1 , 4*COM ,1*VGA, 1*DP, 1*HDMI, Audio out, Mic,GPIO-16,1*remote switch, DC 9-48V
HKA12019063-XB	DC power adapter, DC19V/6.32A,120W