

GV-302SI-C

- ◆ Use board mounted Intel® Celeron J6412 Quad Core 2.0GHz, Burst to 2.6GHz CPU
- ◆ 1×Notebook memory slot, Support DDR4 3200 max 16GB
- ◆ 2×Intel I226-V high performance 2.5G network port
- ◆ 1×SATA 1×M.2 2280 Support SATA3.0
- ◆ 1×HDMI, 1×VGA, Support synchronous/asynchronous display function
- ◆ 1×M.2 Key-B 3042/3052, Support 4G/5G
- ◆ 1×M.2 Key-E 2230, Support Wi-Fi&BT
- ◆ Support watchdog, diskless startup, wake-on-LAN, power on startup, and timing startup
- ◆ All aluminum alloy, fan free design for the entire machine, supporting desktop, wall mounted, and rail mounted installation
- ◆ Suitable for applications such as IoT, control, and Industry 4.0



Detailed specifications

Processor System

CPU	Board mounted Intel® Celeron J6412 Quad Core 2.0GHz, Burst to 2.6GHz CPU
-----	--

Memory

Slot Number	1×Notebook memory slot, Support DDR4 3200 max 16GB
-------------	--

Graphics

VGA	Analog signal display interface, VGA+HDMI Supports synchronous/asynchronous dual display function
HDMI	High definition multimedia display interface, side standing standard HDMI interface

Storage

HDD	1×M.2 2280 Support SATA3.0 1×SATA
-----	--------------------------------------

Face-plate

DC_IN	1*DC2.5 metal threaded joint, 9-36V input
VGA	1*DB15
HDMI	1*HDMI 2.0b
LAN	2*RJ45 Gigabit Ethernet port
USB	2*USB3.0(Double layer TYPE-A interface)
USB	4* USB2.0(Double layer TYPE-A interface)
Audio	1*Line-MIC
PWR SW+PWR LED	1*4P Phoenix terminal

COM	6*COM (Standard RS232 mode, optional RS232/RS485 mode for COM2 and COM3)
PWR	1* PWR SW+1*PWR LED
Physical characteristics	
Size (w*d*h)/Weight	Without ear stand : 168.6×120.1×41.5 Ear stand included : 190.2×120.1×44.5mm approximately 0.60KG
Material/Surface Treatment	High quality aluminum extruded alloy/sandblasting oxidation
Environment	
Working	Temperature: -20~60 °C, humidity: 5%~95%, non condensing
Storage	Temperature: -20~85°C , humidity:5%~95% , non condensing

Size

